

**DATA STREAM CONTROL SYSTEM FOR ASSOCIATING COUNTER  
VALUES WITH STORED SELECTED DATA PACKETS FROM AN  
INCOMING DATA TRANSPORT STREAM TO PRESERVE INTERPACKET  
TIME INTERVAL INFORMATION**

Background of the Invention

Field of the Invention

The present invention is directed to information storage and display systems utilizing storage devices, and more particularly, to video recording systems that store and playback streaming video data packets.

Description of the Related Art

Audiovisual information is advantageously compressed by audiovisual data storage systems, thereby expressing the information by using less data. Compression reduces the amount of storage needed for a given amount of source material, and it reduces the bandwidth needed for the transfer of the data. One standard for audiovisual compression is MPEG (Moving Picture Experts Group) compression which was developed by a joint technical committee of the International Organization for Standardization (ISO) and the International Electrotechnical Commission (IEC). The MPEG compression standard is outlined in "Information Technology: Generic Coding of Moving Pictures and Associated Audio Information: Systems," International Standard ISO/IEC 13818-1:1996 (E), which is incorporated by reference herein.

For the transmission of audiovisual programming, various programs transmitted from the outputs of various MPEG encoders are multiplexed together into a transport stream, the transport stream comprising multiple series of fixed-size data packets, along with metadata which describes the transport stream. Each data packet comprises a header and a payload. The header contains various information regarding the data packet, including the packet identifier code (PID) which identifies the program or data to which the data packet belongs. The metadata includes a program association table (PAT) that lists the various programs comprising the transport stream and points to a

1 program map table (PMT) that lists the corresponding data packets. The metadata can  
2 also include conditional access information (i.e., encryption).

3 The different series of data packets of the transport stream are generally  
4 generated by different MPEG encoders, which typically have different compression  
5 factors and different system time clocks (STCs). The different system time clocks  
6 generally are not synchronized to one another. In changing from one program to the  
7 next, an MPEG decoder synchronizes its STC with the STC which was used during the  
8 encoding of each program. This synchronization avoids jitter in the decoded data  
9 stream, and avoids overrun or underrun of the memory buffers of the MPEG decoder.  
10 To provide the synchronization data needed to decode a series of data packets, the data  
11 packets are encoded with program clock reference (PCR) information.

12 During the encoding of audiovisual data, a fixed-frequency (e.g., 27 MHz) STC  
13 of an MPEG encoder drives a constantly running binary counter, the value of which is  
14 sampled periodically and placed in the data packet headers as PCR information. At the  
15 decoder, the PCR value of a data packet is compared with a local PCR value which is  
16 driven by a STC with nominally the same frequency. The difference in these PCR values  
17 (the PCR phase error) thereby allows the MPEG decoder to properly synchronize its  
18 STC to the STC of the MPEG encoder for the selected series of data packets, thereby  
19 duplicating the same frame rate used at the MPEG encoder with the frame rate generated  
20 at the MPEG decoder. Note that because the timing of the presentation of these PCR  
21 values at the MPEG decoder is critical for the MPEG decoder to operate correctly, this  
22 PCR method relies on the MPEG decoder receiving the series of data packets for a  
23 particular program with the same interpacket time intervals as the series of data packets  
24 had when they were transmitted from the MPEG encoder.

25 U.S. Patent No. 5,467,137 issued to Zdepski, which is incorporated by reference  
26 herein, addresses the problem of varying transmission times among a series of data  
27 packets being transmitted across a system such as the Internet. Zdepski discloses an  
28 apparatus and method for providing synchronization for a transmitted multilayered  
29 compressed video signal by inserting auxiliary transport packets which include modifiable  
30 differential time codes or count values. These differential count values are used to

1 account for the incremental delays the transport packets incur during the signal  
2 forming/transmission process.

3  
4 Summary of the Invention

5 The present invention may be regarded as a data stream control system  
6 connectable to a storage device, the data stream control system selectively storing a  
7 series of selected data packets from an incoming data transport stream. A transport  
8 stream input interface receives the incoming data transport stream comprising selected  
9 data packets having interpacket time intervals between the selected data packets. A  
10 command interface receives at least one packet filter parameter identifying the series of  
11 selected data packets. A programmable data packet filter is coupled to the command  
12 interface and transport stream input interface and transmits the series of selected data  
13 packets in response to the packet filter parameter and the incoming data transport  
14 stream. A storage interface is coupled to the programmable data packet filter and is  
15 connectable to the storage device. The storage interface transmits the selected data  
16 packets to the storage device. A counter provides counter values for the selected data  
17 packets. Each counter value represents a time of reception of a respective selected data  
18 packet. The counter value is stored in association with the respective selected data  
19 packet to preserve information regarding the interpacket time intervals of the series of  
20 selected data packets from the incoming data transport stream.

21 The present invention may also be regarded as a data storage system that  
22 selectively stores a series of selected data packets from an incoming data transport  
23 stream and that plays back and transmits the stored series of selected data packets to an  
24 outgoing data transport stream. A data storage system controller generates at least one  
25 packet filter parameter in response to user input. The at least one packet filter parameter  
26 identifies the series of selected data packets. A transport stream input interface receives  
27 the incoming data transport stream comprising selected data packets having interpacket  
28 time intervals between the selected data packets. A command interface receives the at  
29 least one packet filter parameter from the data storage system controller. A  
30 programmable data packet filter is coupled to the command interface and transport  
31 stream input interface and transmits the series of selected data packets in response to the

1 packet filter parameter and the incoming data transport stream. A storage device stores  
2 the selected data packets. A storage interface is coupled to the programmable data  
3 packet filter and to the storage device and transmits the selected data packets to the  
4 storage device and receives stored selected data packets from the storage device. A  
5 counter provides counter values for the selected data packets. Each counter value  
6 represents a time of reception of a respective selected data packet. The counter value is  
7 stored in association with the respective selected data packet to preserve information  
8 regarding the interpacket time intervals of the series of selected data packets from the  
9 incoming data transport stream. A timing restorer receives the stored selected data  
10 packets from the storage interface and receives the counter values stored in association  
11 with the respective selected data packets. The timing restorer transmits the stored  
12 selected data packet at a time of transmission responsive to the respective counter value.  
13 A transport stream output interface is coupled to the timing restorer and the outgoing  
14 data transport stream. The transport stream output interface receives the stored series of  
15 selected data packets from the timing restorer. The outgoing data transport stream  
16 receives the stored series of selected data packets from the transport stream output  
17 interface with interpacket time intervals which substantially match the corresponding  
18 interpacket time intervals of the series of selected data packets from the incoming data  
19 transport stream.

20 The present invention may also be regarded as a method of selectively storing a  
21 series of selected data packets from an incoming data transport stream. The series of  
22 selected data packets has interpacket time intervals between the selected data packets.  
23 The method comprises receiving at least one packet filter parameter identifying the series  
24 of selected data packets. The method further comprises receiving the incoming data  
25 transport stream. The method further comprises storing the series of selected data  
26 packets in response to the packet filter parameter and the incoming data transport  
27 stream. The method further comprises providing counter values for the selected data  
28 packets. Each counter value represents a time of reception of a respective selected data  
29 packet. The method further comprises storing the counter value in association with the  
30 respective selected data packet, thereby preserving information regarding the interpacket

1 time intervals of the series of selected data packets from the incoming data transport  
2 stream.

3 The present invention may also be regarded as a method of selectively storing  
4 and playing back a series of selected data packets from an incoming data transport  
5 stream. The series of selected data packets has interpacket time intervals between the  
6 selected data packets. The method comprises receiving at least one packet filter  
7 parameter identifying the series of selected data packets. The method further comprises  
8 receiving the incoming data transport stream. The method further comprises storing the  
9 series of selected data packets in response to the packet filter parameter and the  
10 incoming data transport stream. The method further comprises providing counter values  
11 for the selected data packets. Each counter value represents a time of reception of a  
12 respective selected data packet. The method further comprises storing the counter value  
13 in association with the respective selected data packet, thereby preserving information  
14 regarding the interpacket time intervals of the series of selected data packets from the  
15 incoming data transport stream. The method further comprises playing back the stored  
16 selected data packets. The method further comprises receiving the counter value stored  
17 in association with the respective selected data packets. The method further comprises  
18 transmitting the stored selected data packet at a time of transmission responsive to the  
19 respective counter value. The stored series of selected data packets are transmitted with  
20 interpacket time intervals which substantially match the corresponding interpacket time  
21 intervals of the series of selected data packets from the incoming data transport stream.

#### 22 Brief Description of the Drawings

24 Figure 1 schematically illustrates a data storage system comprising a data stream  
25 control system in accordance with an embodiment of the present invention.

26 Figure 2 is a timing diagram of one embodiment of an MPEG-encoded incoming  
27 data transport stream.

28 Figure 3 schematically illustrates a data storage system comprising a data stream  
29 control system in accordance with another embodiment of the present invention.

Figure 4 schematically illustrates a data stream control system in accordance with an embodiment of the present invention, in which the counter is synchronized to a clock that provides time information.

Figure 5 schematically illustrates an exemplary series of selected data packets stored on the storage device.

Figure 6 schematically illustrates a data stream control system in accordance with an embodiment of the present invention, in which the counter is coupled to the programmable data packet filter.

Figure 7 schematically illustrates a data stream control system in accordance with an embodiment of the present invention, in which the timing restorer is synchronized to a clock that provides time information.

Figure 8 schematically illustrates a data stream control system in accordance with an embodiment of the present invention, in which the timing restorer comprises a null data packet generator.

Figure 9 is a flowchart which illustrates one embodiment of a method of selectively storing a series of selected data packets.

Figure 10 is a flowchart which illustrates one embodiment of a method of selectively storing and playing back a stored series of selected data packets.

#### Detailed Description of an Embodiment

Figure 1 schematically illustrates a data storage system 2 comprising a data stream control system 10 in accordance with an embodiment of the present invention. The data stream control system 10 is connectable to a storage device 20 and selectively stores a series of selected data packets 30 from an incoming data transport stream 40. The data stream control system 10 comprises a transport stream input interface 60 that receives the incoming data transport stream 40 that has interpacket time intervals between the selected data packets 30. The data stream control system 10 further comprises a command interface 50 that receives the at least one packet filter parameter 52 identifying the series of selected data packets 30. The data stream control system 10 further comprises a programmable data packet filter 70 coupled to the command interface 50 and transport stream input interface 60. The programmable data packet

1 filter 70 transmits the series of selected data packets 30 in response to the packet filter  
2 parameter 52 and the incoming data transport stream 40. The data stream control  
3 system 10 further comprises a storage interface 80 coupled to the programmable data  
4 packet filter 70 and connectable to the storage device 20. The storage interface 80  
5 transmits the selected data packets 30 to the storage device 20. The data stream control  
6 system 10 further comprises a counter 90 that provides counter values 100 for the  
7 selected data packets 30. Each counter value 100 represents a time of reception of a  
8 respective selected data packet 30. The counter value 100 is stored in association with  
9 the respective selected data packet 30 to preserve information regarding the interpacket  
10 time intervals of the series of selected data packets 30 from the incoming data transport  
11 stream 40. The data storage system 2 comprises a data storage system controller 4 that  
12 generates the at least one packet filter parameter 52 identifying the series of selected data  
13 packets 30.

14 In certain embodiments of the present invention, the data stream control system  
15 10 is a portion of a data storage system 2 such as a personal video recorder (PVR). In  
16 these embodiments, the data stream control system 10 can be realized as an application-  
17 specific integrated circuit (ASIC) coupled to other components of the PVR 2. Persons  
18 skilled in the art appreciate, however, that the data stream control system 10 described  
19 herein can also be realized as multiple separate components of the PVR 2. Only the  
20 portions of the PVR 2 pertinent to the present invention are illustrated in Figure 1 and  
21 the other figures. One skilled in the art will appreciate that an exemplary PVR 2 has  
22 other elements (not shown) that implement other features of the PVR 2. An exemplary  
23 PVR 2 is disclosed in copending U.S. Patent Application No. 09/585,249, filed May 31,  
24 2000, entitled "Digital Video Recorder Connectable To An Auxiliary Interface Of A Set-  
25 Top Box That Provides Video Data Stream To A Display Device Based On Selection  
26 Between Recorded Video Signal Received From The Digital Video Recorder And A  
27 Real-Time Video Signal," which is incorporated by reference herein. Also, in other  
28 embodiments, the data stream control system 10 can be a portion of other types of data  
29 storage systems, such as personal computers or video camera systems.

30 The data stream control system 10 is connectable to a storage device 20 which  
31 selectively stores a series of selected data packets 30 from an incoming data transport

1 stream 40. In addition, the storage device 20 can provide storage for various types of  
2 system information. In certain embodiments of the present invention, the storage device  
3 20 comprises a hard disk drive compatible with a version of the ATA (AT-attachment)  
4 standard, such as IDE (Integrated Drive Electronics). In other embodiments, the storage  
5 device 20 comprises a hard disk drive compatible with the SCSI (Small Computer  
6 System Interface) standard. In still other embodiments, the storage device 20 comprises  
7 a hard disk drive compatible with the IEEE 1394 standard, which is described in the  
8 "IEEE Std 1394-1995 IEEE Standard for a High Performance Serial Bus," August 30,  
9 1996, which is incorporated by reference herein. A storage device 20 compatible with  
10 the present invention can utilize any technology that provides writable non-volatile  
11 storage (e.g., a writable digital video disk (DVD) drive).

12 In an embodiment in which the data stream control system 10 is a portion of a  
13 PVR 2, the incoming data transport stream 40 is typically generated by a video input  
14 interface in response to an external video data stream received from a video data service  
15 provider that supplies video programming to multiple users. Examples of such video  
16 data service providers include, but are not limited to, cable television systems and  
17 satellite systems. Alternatively, the external video data stream can be received from  
18 UHF or VHF broadcast signals using an antenna. The incoming data transport stream 40  
19 is generated by the video input interface with a format which is compatible with the other  
20 components of the data storage system. For example, in certain embodiments, to  
21 provide compatibility of the PVR 2 with an analog-formatted external video data stream,  
22 the video input interface of certain embodiments comprises an MPEG (Motion Pictures  
23 Experts Group) encoder, which generates an incoming data transport stream 40  
24 comprising MPEG-encoded data packets in response to the analog-formatted external  
25 video data stream. Alternatively, in other embodiments, the external video data stream  
26 itself comprises MPEG-encoded data packets thereby serving as the incoming data  
27 transport stream 40, which is then transmitted to the data stream control system 10 by  
28 the video input interface. Furthermore, for particular embodiments that are compatible  
29 with an encrypted external video data stream (e.g., video data streams from premium  
30 cable channels), the PVR 2 can also comprise a decrypter, typically as a component of  
31 the video input interface.




1           The transport stream input interface 60 receives the incoming data transport  
2 stream 40 for the data stream control system 10 and transmits the incoming data  
3 transport stream 40 to the programmable data packet filter 70. Persons skilled in the art  
4 are able to provide a video input interface and a transport stream input interface 60 that  
5 are compatible with the present invention. Note that while the following discussion  
6 focuses on certain embodiments in which the incoming data transfer stream 40 is MPEG-  
7 encoded, other embodiments compatible with the present invention can utilize incoming  
8 data transport streams 40 conforming to other selected compression standards.

9           In an embodiment in which the data stream control system 10 is a portion of a  
10 PVR 2, the packet filter parameter 52 is typically generated by a system controller in  
11 response to user input and/or electronic program guide (EPG) information. A user  
12 provides user input to the PVR to select which video program segments are stored from  
13 the incoming data transfer stream 40, as well as to control various other operation  
14 parameters of the PVR 2, such as playback commands (e.g., pause, instant-replay, etc.).  
15 The incoming data transport stream 40 comprises selected data packets 30  
16 corresponding to the video program segments selected to be stored, and non-selected  
17 data packets corresponding to the portion of the incoming data transport stream 40 not  
18 selected for storing. The EPG information is a database, typically displayed to the user  
19 in the form of a program grid, containing information regarding the programs and  
20 broadcast schedules from various broadcast channels. The user input, in conjunction  
21 with the EPG information, is used by the system controller to generate at least one  
22 packet filter parameter 52 which indicates the series of selected data packets 30  
23 corresponding to the video program segment selected for storing. The packet filter  
24 parameter 52 is then transmitted to the command interface 50 of the data stream control  
25 system 10.

26           In embodiments in which the incoming data transport stream 40 comprises  
27 multiple series of MPEG-encoded data packets, the packet filter parameter 52 comprises  
28 the packet identifier code (PID) which is contained in the header of each selected data  
29 packet 30. Each MPEG-encoded data packet contains 188 bytes, comprising a header  
30 with a minimum size of 4 bytes, and a payload which comprises the encoded data. The  
31 header comprises the PID and the program clock reference (PCR) for the particular data

1 packet. As described above, an MPEG decoder relies on the PCR value to properly  
2 synchronize its system time clock (STC) to the STC of the MPEG encoder. Under the  
3 MPEG encoding standard, in a given transport stream, MPEG-encoded data packets  
4 belonging to a given elementary stream (i.e., generated by the same MPEG encoder) will  
5 have the same PID. Packets in another elementary stream will have another PID. In this  
6 way, a decoder or demultiplexer can select the elementary stream it wants from a  
7 transport stream and reject the remainder. Under the MPEG standard, the PID is a  
8 thirteen-bit code which distinguishes the various data packets. For example, null data  
9 packets all have the same PID, which is 8191, or thirteen 1's. Persons skilled in the art  
10 appreciate that other encoding or compression standards with other packet identification  
11 means are compatible with the present invention.

12 Figure 2 is a timing diagram of one possible embodiment of an MPEG-encoded  
13 incoming data transport stream 40 comprising audiovisual (AV) program data segments  
14 AV1 and AV2, information technology (IT) data segments IT1 and IT2, and null data  
15 packets. Null data packets are typically part of an incoming data transport stream 40 in  
16 which the full bandwidth of the incoming data transport stream 40 is not being utilized by  
17 the video data streams being transmitted. As a result, an incoming data transport stream  
18 40 which contains video data streams being transmitted with reduced resolution, and  
19 hence requiring less bandwidth, will generally incorporate more null data packets. The  
20 horizontal axis of Figure 2 corresponds to time, with increasing elapsed time from left to  
21 right. In the following discussion, the series of AV1 data packets (AV1-1, AV1-2, ...)   
22 represents the series of selected data packets 30 corresponding to the video program  
23 segment selected for storing to better illustrate the operation of the data stream control  
24 system 10. The AV1 series of selected data packets 30 has interpacket time intervals  
25 between the various AV1 data packets. Under one convention of expressing the  
26 interpacket time intervals, an interpacket time interval is defined as the time interval  
27 between the time of reception of the sync reference of a first selected data packet and the  
28 time of reception of the sync reference of a second selected data packet. Typically, the  
29 sync reference is the first byte of each data packet; however, any portion of the data  
30 packets may be selected as the sync reference as long as the selection is consistent for all  
31 data packets. For example, the interpacket time interval between selected data packets

1 AV1-1 and AV1-2 is  $(t_2 - t_1)$ , where  $t_1$  and  $t_2$  are the times of reception of the sync  
2 references of the AV1-1 and AV1-2 selected data packets, respectively.

3 As seen in Figure 2, these interpacket time intervals comprise one selected data  
4 packet, non-selected data packets (i.e., AV2, IT1, IT2, null) and/or time periods with no  
5 data packets (denoted in Figure 2 as an ellipsis). For example, the interpacket time  
6 interval between times  $t_1$  and  $t_2$  comprises the AV1-1 selected data packet and the AV2,  
7 IT1, and IT2 non-selected data packets. The interpacket time interval between times  $t_3$   
8 and  $t_4$  comprises the AV1-3 selected data packet, an AV2 non-selected data packet, and  
9 a time period with no data packets. Note that for selected data packets which  
10 immediately precede one another (e.g., selected data packets AV1-4 and AV1-5), the  
11 corresponding interpacket time interval between times  $t_4$  and  $t_5$  comprises one selected  
12 data packet (e.g., AV1-4). Accordingly, another convention can express the interpacket  
13 time intervals in terms of a number of non-selected data packets interposed between a  
14 first selected data packet and a second selected data packet. For example, the  
15 interpacket time interval between times  $t_1$  and  $t_2$  can be expressed as three non-selected  
16 data packets, and the interpacket time interval between times  $t_4$  and  $t_5$  can be expressed  
17 as zero. Persons skilled in the art appreciate that various conventions for expressing the  
18 interpacket time intervals are compatible with the present invention.

19 The incoming data transport stream 40 and the packet filter parameter 52 are  
20 received by the programmable data packet filter 70, which transmits the series of selected  
21 data packets 30 in response to the packet filter parameter 52 and the incoming data  
22 transport stream 40. For the incoming data transport stream 40 illustrated in Figure 2,  
23 the programmable data packet filter 70 receives the selected data packets 30 (i.e., AV1-  
24 1, AV1-2, ...) at times  $t_1, t_2, \dots$  and the interpacket time intervals between the selected  
25 data packets 30 comprise the non-selected data packets. In certain embodiments, the  
26 programmable data packet filter 70 comprises a demultiplexer which transmits the series  
27 of selected data packets 30 to the storage interface 80, but does not transmit the non-  
28 selected data packets. For the incoming data transport stream 40 illustrated in Figure 2,  
29 the programmable data packet filter 70 transmits the AV1 series of selected data packets  
30 30 but does not transmit the AV2, IT1, IT2, or null data packets. Furthermore, in

1 certain embodiments as described below, the programmable data packet filter 70 detects  
2 non-selected data packets and generates a corresponding signal.

3 The storage interface 80 is coupled to the programmable data packet filter 70 and  
4 is connectable to the storage device 20. The storage interface 80 transmits the selected  
5 data packets 30 to the storage device 20. As is more fully described in the following  
6 discussion of various embodiments, the storage interface 80 can comprise various  
7 memory buffers to facilitate the transfer of selected data packets and other information  
8 between the data stream control system 10 and the storage device 20. In certain  
9 embodiments, the storage interface 80 can also be coupled to other memory buffers (e.g.,  
10 random-access memory (RAM)) to store various information such as the counter values  
11 100. Persons skilled in the art are able to provide a storage interface 80 compatible with  
12 the present invention.

13 The counter 90 provides counter values 100 for the selected data packets 30.  
14 Each counter value 100 represents a time of reception of a respective selected data  
15 packet 30. In one embodiment, the time of reception of a data packet is a time at which  
16 the data packet is received by the programmable data packet filter 70. In other  
17 embodiments, the time of reception can be the time at which the data packet is received  
18 by another component of the data storage system 2, as long as the time of reception is  
19 consistently defined for all data packets. As is more fully described in the following  
20 discussion of various embodiments, the counter values 100 can represent the times of  
21 reception of the selected data packets 30 in numerous forms. In addition, in these  
22 various embodiments, the counter 90 can be coupled with various other components of  
23 the data stream control system 10 in order to provide counter values 100 compatible  
24 with the present invention. As illustrated in Figure 1, two of these optional couplings are  
25 represented by the dashed line between the counter 90 and the programmable data  
26 packet filter 70 and the dashed line between the counter 90 and the transport stream  
27 input interface 60. Persons skilled in the art appreciate that other embodiments can  
28 utilize alternative couplings of the counter 90 which are compatible with the present  
29 invention.

30 The counter values 100 are stored in association with the respective selected data  
31 packets 30 to preserve information regarding the interpacket time intervals of the series

1 of selected data packets 30 from the incoming data transport stream 40. As is described  
2 more fully below, certain embodiments can append the counter values 100 to the  
3 selected data packets 30, storing both on the storage device 20. Alternatively, in other  
4 embodiments, the counter values 100 can be stored on a memory buffer separate from  
5 the storage drive 20 in a memory location indexed to the respective selected data packet  
6 30.

7 Figure 3 schematically illustrates a data storage system 2 comprising an  
8 embodiment of the data stream control system 10 in which the storage interface 80  
9 receives stored selected data packets 110 from the storage device 20, and the storage  
10 device 20 plays back and transmits the stored series of selected data packets 110. In this  
11 embodiment, the data stream control system 10 further comprises a timing restorer 120  
12 that receives the stored selected data packets 110 from the storage interface 80 and that  
13 receives the counter value 130 stored in association with the respective selected data  
14 packets 110. The timing restorer 120 transmits the stored selected data packet 110 at a  
15 time of transmission responsive to the respective counter value 130. The data stream  
16 control system 10 illustrated in Figure 3 further comprises a transport stream output  
17 interface 140 coupled to the timing restorer 120 and an outgoing data transport stream  
18 150. The transport stream output interface 140 receives the stored series of selected  
19 data packets 110 from the timing restorer 120 and transmits the stored series of selected  
20 data packets 110 to the outgoing data transport stream 150. The stored series of  
21 selected data packets 110 transmitted to the outgoing data transport stream 150 has  
22 interpacket time intervals which substantially match the corresponding interpacket time  
23 intervals of the series of selected data packets from the incoming data transport stream.

24 As is described more fully in the following discussion of various embodiments,  
25 various configurations of the timing restorer 120 can utilize the stored counter values  
26 130 to substantially match the interpacket time intervals of the corresponding series of  
27 selected data packets. In certain embodiments, by transmitting a stored selected data  
28 packet 110 in response to the respective stored counter value 130, the timing restorer  
29 120 can substantially restore the interpacket time intervals which existed between the  
30 corresponding selected data packets 30 as they were received by the programmable data  
31 packet filter 70. Alternatively, in other embodiments, the timing restorer 120 can

1 substantially restore the interpacket time intervals by inserting null data packets between  
2 the stored selected data packets 110 in response to the respective stored counter value  
3 130. In the various embodiments, the interpacket time intervals of the series of selected  
4 data packets 30 are substantially matched or restored when the stored selected data  
5 packets 110 have interpacket time intervals which match the interpacket time intervals of  
6 the corresponding selected data packets 30 to within approximately one clock cycle.

7 The transport stream output interface 140 receives the stored series of selected  
8 data packets 110 with interpacket time intervals which substantially match those of the  
9 corresponding series of selected data packets and transmits the stored series of selected  
10 data packets 110 to the outgoing data transport stream 150. In certain embodiments in  
11 which the data stream control system 10 is a portion of a PVR, the outgoing data  
12 transport stream 150 transmitted from the data stream control system 10 is received by  
13 an MPEG decoder which in response generates an audiovisual data stream which is  
14 displayed on a display device, such as a television. In this way, the data stream control  
15 system 10 enables a PVR user to view a previously stored video data segment. Persons  
16 skilled in the art are able to provide a transport stream output interface 140 that is  
17 compatible with the present invention.

18 As described above, MPEG decoding requires that the interpacket time intervals  
19 of the series of selected data packets 30 be preserved because an MPEG decoder utilizes  
20 the PCR values of the selected data packet 30 to synchronize its STC with the STC of  
21 the MPEG encoder. Normally, when a series of selected data packets 30 from an  
22 incoming data transport stream 40 is stored on a storage device 20, the selected data  
23 packets 30 are collected in a memory buffer and then burst out to the media within the  
24 storage device 20. This procedure removes any information regarding the interpacket  
25 time intervals of the series of selected data packets 30 that was present in the incoming  
26 data transport stream 40. Consequently, the PCR timing for MPEG encoding and  
27 decoding is therefore compromised. However, by storing the counter values 100  
28 representing the times of reception in association with the selected data packets 30, the  
29 data stream control system 10 compatible with the present invention preserves  
30 information regarding the interpacket time intervals of the series of selected data packets  
31 30 from the incoming data transport stream 40. Also, by not storing the non-selected

1 data packets and the time periods without data packets, this use of counter values 100  
2 stored in association with the selected data packet 30 can further reduce the total amount  
3 of storage space required. Persons skilled in the art recognize that in certain  
4 embodiments, this preservation of information regarding the interpacket time interval can  
5 find utility with data streams which are encoded according to other selected compression  
6 standards.

7 In the embodiment of the data stream control system 10 illustrated in Figure 4,  
8 the data stream control system 10 further comprises a clock 160, and the storage  
9 interface 80 further comprises a storage memory buffer 170 and a playback memory  
10 buffer 180. The clock 160 is coupled to the counter 90 and provides time information in  
11 the form of a clock value 190. In this way, the counter 90 is synchronized to the clock  
12 160. In addition, the counter 90 of the embodiment illustrated in Figure 4 is coupled to  
13 the programmable data packet filter 70. Note that in alternative embodiments, the  
14 counter 90 need not be coupled to the programmable data packet filter 70. The clock  
15 160 illustrated in Figure 4 is a separate component of the data stream control system 10;  
16 however, in other embodiments, the clock 160 can be a sub-component of the counter  
17 90, system controller, or other component of the data stream control system 10. In  
18 certain other embodiments, the clock 160 can be external to the data stream control  
19 system 10.

20 The programmed data packet filter 70 of the embodiment illustrated in Figure 4  
21 sends a signal to the counter 90 upon receiving a selected data packet 30. In response to  
22 this signal, the counter 90 determines the time of reception by the programmed data  
23 packet filter 70 of the selected data packet 30 by noting the clock value 190 from the  
24 clock 160. As described below, different embodiments of the present invention can  
25 express this time of reception of the selected data packet 30 in different forms.

26 In certain embodiments, the counter value 100 corresponding to the selected data  
27 packet 30 represents a time interval expressed as an absolute clock value 190 in relation  
28 to a reference time, such as the time  $t_0$  of a previous reset of the clock 160. For  
29 example, referring to Figure 2, the time of reception  $t_1$  by the programmable data packet  
30 filter 70 of the selected AV1-1 data packet would be represented by a counter value of  
31  $(t_1 - t_0)$ , the time of reception  $t_2$  by the programmable data packet filter 70 of the selected

1 AV1-2 data packet would be represented by a counter value of  $(t_2-t_0)$ , and so on. The  
2 selected data packet 30 and its associated counter value 100 are then transmitted by the  
3 programmable data packet filter 70 and the counter 90 to the storage memory buffer  
4 170.

5 Alternatively, in other embodiments, the counter value 100 corresponding to the  
6 selected data packet 30 represents a time interval expressed as a differential clock value  
7 190 in relation to a reference time, such as the time of reception of an earlier selected  
8 data packet 30. For example, referring to Figure 2, where the reference time is the time  
9 of reception  $t_1$  of the selected AV1-1 data packet, the selected AV1-1 data packet would  
10 be associated with a counter value of  $(t_1-t_1)=0$ , the selected AV1-2 data packet detected  
11 at  $t_2$  would be associated with a counter value of  $(t_2-t_1)$ , the selected AV1-3 data packet  
12 detected at  $t_3$  would be associated with a counter value of  $(t_3-t_1)$ , and so on. Where the  
13 reference time is the time of reception of the immediately preceding selected data packet  
14 30, the selected AV1-2 data packet would be associated with a counter value of  $(t_2-t_1)$ ,  
15 the selected AV1-3 data packet detected at  $t_3$  would be associated with a counter value  
16 of  $(t_3-t_2)$ , and so on. The selected data packet 30 and its associated counter value 100  
17 are then transmitted by the programmable data packet filter 70 and the counter 90 to the  
18 storage memory buffer 170.

19 Note that where a second selected data packet immediately follows another with  
20 no intervening time or non-selected data packets (e.g., selected data packets AV1-4 and  
21 AV1-5 in Figure 2), the interpacket time interval is the time corresponding to a single  
22 selected data packet. In certain embodiments of the present invention, this time  
23 corresponding to a single selected data packet can be implicit in the counter values, so  
24 that the corresponding counter value can be expressed as zero. Alternatively, in other  
25 embodiments of the present invention, the second of these selected data packets may not  
26 have a counter value associated with it. Instead, a flag or other form of indication may  
27 be used to denote two adjacent selected data packets with no intervening time or non-  
28 selected data packets. Persons skilled in the art will appreciate that such an embodiment  
29 is compatible with the present invention.

30 The storage memory buffer 170 continuously transfers selected data packets 30  
31 from the data stream control system 10 to the storage device 20. Similarly, the playback



1 memory buffer 180 continuously transfers stored selected data packets 110 from the  
2 storage device 20 to the data stream control system 10. Data streaming rates for  
3 continuously streaming video data (e.g., 1 Mb/s) are typically much lower than the  
4 instantaneous data transfer rates for transferring data packets from storage devices 20  
5 comprising hard disk drives (e.g., 66 Mb/s). The storage memory buffer 170 and the  
6 playback memory buffer 180 thus serve as temporary repositories of selected data  
7 packets in order to maintain a data streaming rate that is lower than the instantaneous  
8 data transfer rate of the storage device 20. Similar memory buffers are described in U.S.  
9 Patent Application No. 09/628,583, filed July 31, 2000, entitled "Video Recording  
10 System Utilizing Host-Processor-Resident Error Recovery To Transfer Non-Time-  
11 Critical, Error-Intolerant Data Segments While Transferring Time-Critical, Error-  
12 Tolerant Streaming Data Segments At A Required Data Transfer Rate," which is  
13 incorporated by reference herein.

14 From the storage memory buffer 170, the selected data packets 30 are  
15 transmitted to the storage device 20, where they are stored for playback upon  
16 appropriate commands from the data stream control system 10. In addition, the  
17 corresponding counter values 100 are directed by the storage interface 80 to be stored in  
18 association with the selected data packets 30. In the embodiment of the data stream  
19 control system 10 illustrated in Figure 4, the selected data packets 30 and the respective  
20 counter values 100 are both transmitted to the storage device 20. A storage interface 80  
21 compatible with this embodiment can comprise a multiplexer to combine the selected  
22 data packets 30 with the respective counter values 100 which are both then stored on the  
23 storage device 20. In certain embodiments compatible with MPEG-encoded selected  
24 data packets 30, an MPEG-encoded selected data packet is appended with a  
25 corresponding counter value representing the time of reception of the selected data  
26 packet, and both the selected data packet and the counter value are stored on the storage  
27 device 20. Figure 5 schematically illustrates an exemplary series of selected data packets  
28 110 stored with the corresponding counter values 130 by the storage device 20, the  
29 selected data packets corresponding to the video program segment AV1 of Figure 2. In  
30 certain embodiments of the present invention, the counter value 130 is a 4-byte value  
31 appended to the front end of the 188-byte selected data packet 110. Figure 5 illustrates

1 an embodiment in which the counter value 130 stored with the stored selected data  
2 packet 110 is expressed as an absolute clock value 190 in relation to a reference time  $t_0$ ,  
3 although other embodiments are also compatible with the present invention. Note that  
4 embodiments which store the counter values 130 on a memory buffer or RAM at a  
5 memory location indexed to the respective stored selected data packet 110, and not with  
6 the respective stored selected data packets 110 on the storage device 20, are also  
7 compatible with the present invention.

8 In embodiments in which the interpacket time intervals of the series of selected  
9 data packets 30 are completely filled with non-selected data packets, the data stream  
10 control system 10 schematically illustrated in Figure 6 can be used. In this embodiment,  
11 the counter 90 is coupled to the programmable data packet filter 70, which detects non-  
12 selected data packets, i.e., those data packets which do not correspond to the selected  
13 video program segments, and transmits a series of signals 200 to the counter 90, each  
14 signal 200 denoting the detection of a non-selected data packet. By counting the number  
15 of such signals 200 preceding a selected data packet 30 since receiving a previously  
16 received selected data packet 30, the counter 90 can determine the time of reception of  
17 the selected data packet 30. The counter 90 then generates a counter value 100 which  
18 comprises a non-selected packet count associated with the selected data packet 30. For  
19 example, referring to Figure 2, the AV1-2 selected data packet would be associated with  
20 a counter value of 3, which represents the number of non-selected data packets detected  
21 since the time of reception of the AV1-1 selected data packet, the AV1-3 selected data  
22 packet would be associated with a counter value of 2, which represents the number of  
23 non-selected data packets detected since the time of reception of the AV1-2 selected  
24 data packet, and so on.

25 Alternatively, in other embodiments, the programmable data packet filter 70  
26 detects every data packet, both selected data packets 30 and non-selected data packets,  
27 and transmits a series of signals to the counter 90, each signal denoting the detection of a  
28 data packet. By generating a counter value 100 which corresponds to a continual count  
29 of the number of data packets, the counter 90 can express the time of reception for a  
30 selected data packet 30 as the ordinal number of the selected data packet 30 in the  
31 incoming data transport stream 40. For example, referring to Figure 2, where the ordinal

1 number of the AV1-1 selected data packet in the incoming data transport stream is  $N_1$ ,  
2 the AV1-2 selected data packet would be associated with a counter value of  $N_2=(N_1+4)$   
3 which is the ordinal number of the AV1-2 selected data packet, the AV1-3 selected data  
4 packet would be associated with a counter value of  $N_3=(N_1+7)$ , which represents the  
5 ordinal number of the AV1-3 selected data packet, and so on. Similarly, in still other  
6 embodiments, the counter value 100 can express the time of reception of a selected data  
7 packet 30 as a difference of the ordinal numbers from two sequential selected data  
8 packets 30. In each of these embodiments, the counter 90 generates a counter value 100  
9 which comprises a non-selected packet count associated with the selected data packet  
10 30. The selected data packet 30 with its respective counter value 100 is then transmitted  
11 by the programmable data packet filter 70 and the counter 90 to the storage memory  
12 buffer 100. Note that embodiments which utilize the non-selected packet count as a  
13 measure of the time of reception would not provide an accurate measure of interpacket  
14 time intervals which are not fully filled with non-selected data packets, such as the time  
15 interval between the AV1-3 selected data packet and the AV1-4 selected data packet, as  
16 illustrated in Figure 2.

17 To playback a stored series of selected data packets 110, the data stream control  
18 system 10 transmits the stored series of selected data packets 110 to the outgoing data  
19 transport stream 150. In the embodiment schematically illustrated in Figure 7, the stored  
20 selected data packets 110 and the corresponding counter values 130 are transmitted by  
21 the storage device 20 to the playback memory buffer 180, which then transmits the  
22 stored selected data packets 110 and corresponding counter values 130 to the timing  
23 restorer 120. Alternatively, in other embodiments in which the counter values 130 are  
24 stored in another memory buffer or RAM, the storage interface 80 receives the counter  
25 values 130 from the memory buffer or RAM and transmits the counter values 130 to the  
26 timing restorer 120.

27 Upon receiving the stored selected data packet 110 with its corresponding  
28 counter value 130, the timing restorer 120 transmits the stored selected data packet 110  
29 to the transport stream output interface 140 at a time of transmission responsive to the  
30 counter value 130 of the stored selected data packet 110. In embodiments in which the  
31 stored selected data packets 110 have been combined with the respective counter values

1 130, the timing restorer 120 can comprise a demultiplexer to separate the stored selected  
2 data packets 110 from the counter values 130. In certain embodiments, the timing  
3 restorer 120 is synchronized to a clock 210, which provides time information which is  
4 used to determine the time of transmission for the stored selected data packet 110. In  
5 certain embodiments of the present invention, the timing restorer 120 is synchronized to  
6 the same clock 160 to which the counter 90 is synchronized. In certain other  
7 embodiments, the timing restorer 120 can be synchronized to a different clock 210. The  
8 clock 210 illustrated in Figure 7 is a separate component of the data stream control  
9 system 10; however, in other embodiments, the clock 210 can be a sub-component of the  
10 timing restorer 120, system controller, or other component of the data stream control  
11 system 10. In certain other embodiments, the clock 210 can be external to the data  
12 stream control system 10.

13 In embodiments in which the timing restorer 120 is synchronized to a clock 210,  
14 the time of transmission of a stored selected data packet 110 can be referenced to a  
15 reference time. By monitoring a clock value 220 from the clock 210, the timing restorer  
16 120 can determine the appropriate time of transmission of the stored selected data packet  
17 110 in response to the corresponding counter value 130. In certain embodiments, the  
18 time of transmission is determined in relation to an absolute reference time, which can be  
19 the time of a previous reset of the clock 210. Alternatively, in other embodiments  
20 utilizing a differential reference time, the reference time can be the time of transmission  
21 for an earlier stored selected data packet 130. For example, referring to the stored  
22 selected data packets 130 as illustrated in Figure 5, where the time of transmission of the  
23 AV1-1 stored selected data packet was  $\tau_1$ , the time of transmission  $\tau_2$  for the AV1-2  
24 stored selected data packet would be  $\tau_1 + (t_2 - t_1)$ , the time of transmission  $\tau_3$  for the AV1-3  
25 stored selected data packet would be  $\tau_1 + (t_3 - t_1)$ , and so on. Similarly, if the counter value  
26 130 of the stored selected data packet 110 represents the time of reception as the  
27 number of non-selected data packets or the ordinal number of the stored selected data  
28 packet, the timing restorer 120 can calculate the appropriate time of transmission and  
29 transmit the stored selected data packet 110 accordingly. Irrespective of the form in  
30 which the counter values 130 represent the times of reception, the stored series of  
31 selected data packets 110 are transmitted to the transport stream output interface 140

1 with interpacket time intervals which substantially match the corresponding interpacket  
2 time intervals of the series of selected data packets from the incoming data transport  
3 stream 40.

4 In certain other embodiments, such as that illustrated in Figure 8, the timing  
5 restorer 120 interposes a number of null data packets between the stored selected data  
6 packet 110 and a previously transmitted stored selected data packet 110. The number of  
7 interposed null data packets is responsive to the counter value 130 of the stored selected  
8 data packet 110. In the embodiment schematically illustrated in Figure 8, the timing  
9 restorer 120 comprises a null data packet generator 230 which produces null data  
10 packets in response to the counter values 130. In embodiments in which the counter  
11 value 130 represents the time of reception for a selected data packet as the number of  
12 non-selected data packets detected since receiving the immediately preceding selected  
13 data packet, the number of interposed null data packets between the corresponding  
14 stored selected data packets 110 equals the number of non-selected data packets.  
15 Alternatively, in embodiments in which the counter value 130 represents the times of  
16 reception as either absolute or differential clock values, the number of interposed null  
17 data packets is chosen to substantially match the interpacket time intervals for the  
18 corresponding series of selected data packets. Irrespective of the form in which the  
19 counter value 130 represents the times of reception, the stored series of selected data  
20 packets 110 are transmitted to the transport stream output interface 140 with interpacket  
21 time intervals which substantially match the corresponding interpacket time intervals of  
22 the series of selected data packets from the incoming data transport stream 40.

23 Figure 9 is a flowchart which illustrates one embodiment of a method 300 of  
24 selectively storing a series of selected data packets 30 from an incoming data transport  
25 stream 40 comprising selected data packets 30 and non-selected data packets. The series  
26 of selected data packets 30 has interpacket time intervals between the selected data  
27 packets 30. The method 300 illustrated in Figure 9 is discussed below primarily in  
28 reference to the embodiment of the data stream control system 10 schematically  
29 illustrated in Figure 1. Persons skilled in the art appreciate that while the flowchart  
30 illustrated in Figure 9 presents the procedural blocks in a particular sequence, other

1       embodiments with other sequences of the procedural blocks are compatible with the  
2       present invention.

3               As shown in Figure 9, the method 300 comprises a procedure block 310 which  
4       comprises receiving at least one packet filter parameter 52 identifying the series of  
5       selected data packets 30 corresponding to the video program segment selected for  
6       storing. As described above, the packet filter parameter 52 is typically generated by a  
7       system controller in response to user input and/or EPG information.

8               The method 300 further comprises a procedure block 320 which comprises  
9       receiving the incoming data transport stream 40. As described above, in certain  
10       embodiments, the incoming data transport stream 40 is generated by the video input  
11       interface in response to an external video data stream. Alternatively in other  
12       embodiments, the incoming data transport stream 40 is generated by the system  
13       controller, or by some other device upstream of the data stream control system 10.

14              The method 300 further comprises a procedure block 330 which comprises  
15       storing the series of selected data packets 30 in response to the packet filter parameter  
16       52 and the incoming data transport stream 40. As described above, the series of selected  
17       data packets 30 is stored on the storage device 20 by transmitting the selected data  
18       packets 30 from the programmable data packet filter 70 to the storage interface 80, and  
19       the storage interface 80 transmits the selected data packets 30 to the storage device 20.  
20       In certain embodiments, the selected data packets 30 are transmitted to the storage  
21       device 20 via a storage memory buffer 170.

22              The method 300 further comprises a procedure block 340 which comprises  
23       providing a counter value 100 for the selected data packets 30. Each counter value 100  
24       represents a time of reception of the selected data packet 30. As described above, in  
25       certain embodiments, the counter value 100 for a selected data packet 30 corresponds to  
26       a time interval between the time of reception of the selected data packet 30 and a  
27       reference time. This reference time can represent a time of a previous reset of a clock,  
28       or a time of reception for an earlier selected data packet 30. In addition, in certain  
29       embodiments, the reference time can represent a time of reception for an immediately  
30       preceding selected data packet 30. Alternatively, in other embodiments, the time of

1 reception of the selected data packet 30 can be expressed as a number of non-selected  
2 data packets between the selected data packets 30.

3 The method 300 further comprises a procedure block 350 which comprises  
4 storing the counter value 100 in association with the respective selected data packet 30.  
5 In this way, information regarding interpacket time intervals of the series of selected data  
6 packets 30 from the incoming data transport stream 40 is preserved. As described  
7 above, in certain embodiments, the counter values 100 are stored with the selected data  
8 packets 30 on the storage device 20. Alternatively, in other embodiments, the counter  
9 values 100 are stored elsewhere, but are indexed to be associated with the respective  
10 selected data packets 30.

11 Figure 10 is a flowchart which illustrates one embodiment of a method 400 of  
12 selectively storing and playing back a series of selected data packets 30 from an  
13 incoming data transport stream 40 comprising selected data packets 30 and non-selected  
14 data packets. The series of selected data packets 30 has interpacket time intervals  
15 between the selected data packets 30. The method 400 illustrated in Figure 10 is  
16 discussed below primarily in reference to the embodiment of the data stream control  
17 system 10 schematically illustrated in Figure 3. Persons skilled in the art appreciate that  
18 while the flowchart illustrated in Figure 10 presents the procedural blocks in a particular  
19 sequence, other embodiments with other sequences of the procedural blocks are  
20 compatible with the present invention.

21 As shown in Figure 10, the method 400 comprises a procedure block 410 which  
22 comprises receiving at least one packet filter parameter 52 identifying the series of  
23 selected data packets, a procedure block 420 which comprises receiving the incoming  
24 data transport stream 40, a procedure block 430 which comprises storing the series of  
25 selected data packets 30, a procedure block 440 which comprises providing a counter  
26 value 100 for the selected data packets 30, and a procedure block 450 which comprises  
27 storing the counter value 100 in association with the respective selected data packet 30.  
28 These procedure blocks 410, 420, 430, 440, and 450 mirror the procedure blocks 310,  
29 320, 330, 340, and 350 described above and schematically illustrated in Figure 9.

30 The method 400 further comprises a procedure block 460 which comprises  
31 playing back the stored selected data packets 110. As described above, to playback the

1 stored series of selected data packets 110, the stored selected data packets 110 are  
2 transmitted from the storage device 20 to the storage interface 80. The storage interface  
3 80 transmits the stored selected data packets 110 to the timing restorer 120. In certain  
4 embodiments, the stored selected data packets 110 are transmitted to the timing restorer  
5 120 via a playback memory buffer 180.

6 The method 400 further comprises a procedure block 470 which comprises  
7 receiving the counter value 130 stored in association with the respective selected data  
8 packets 110. As described above, in certain embodiments which store the counter values  
9 130 with the stored selected data packets 110 on the storage device 20, the counter  
10 values are transmitted from the storage device 20 to the timing restorer 120 via the  
11 storage interface 80. Alternatively, in embodiments in which the counter values 130 are  
12 stored elsewhere, but in association with the respective selected data packets 110, the  
13 counter values 130 are transmitted from the memory buffer or RAM from which they are  
14 stored via the storage interface 80 to the timing restorer 120.

15 The method 400 further comprises a procedure block 480 which comprises  
16 transmitting the stored selected data packet 110 at a time of transmission responsive to  
17 the respective counter value 130. As described above, the stored series of selected data  
18 packets 110 are transmitted with interpacket time intervals which substantially match the  
19 corresponding interpacket time intervals of the series of selected data packets from the  
20 incoming data transport stream 40.